



INDUSTRIES 3R

Danville Office

55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793
Fax: 819-839-2797
Toll-free: 800-567-2728
E-mail: info@industries3r.com

FLAT LEVEL GLASS

3R916

Description

These gauge glasses are offered in three types : Reflex, Plain and High Pressure.

Reflex : They are specifically designed to make the reading of liquid levels in industrial applications easier.

Max. 400 psi (steam boilers), 2 500 psi (non-steam).

Plain : These glasses are used as liquid indicators for moderate pressure steam boilers.

Max. 1 000 psi (steam boilers), 2 500 psi (non-steam).

High Pressure : These flat gauge glasses have undergone a rigorous testing to ensure a high quality component.

Max. 1 500 psi (steam boilers), 5 000 psi (non-steam).

Non-asbestos gaskets 1/16" thick are available for all flat gauge glasses.



Specifications

Technical Data

Length	4-1/2", 5-1/2", 6-1/2", 7-1/2", 8-5/8", 9-7/8", 11", 12-5/8", 13-3/8"
Width	1.307" - 1.347"
Thickness	0.656" - 0.688"

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.