



INDUSTRIES 3R

Danville Office

55, route 116 Ouest
Danville (Québec) Canada
J0A 1A0

Phone: 819-839-2793
Fax: 819-839-2797
Toll-free: 800-567-2728
E-mail: info@industries3r.com

OTHERS

SILIPST

Description

This self-adhesive tape adheres very well to the silicone tape TXP125S and to the silicone tubing TXP660S. For best results, we recommend stretching the SILIPST tape during installation for adequate sealing.



Applications

Mostly used to cover seals and to seal extremities, it also prevents oil and other residue infiltrations within the tubing.

Specifications

Technical Data

Temperature	246°C (475°F)
Silipst - 16 Width	1"
Silipst - 16 Thickness	0.020"
Silipst - 16 Tensile strength	Poor
Silipst - 24 Width	1-1/2"
Silipst - 24 Thickness	0.060"
Silipst - 24 Tensile strength	Moderate
Silipst - 16TR Width	1"
Silipst - 16TR Thickness	0.020"

Silipst - 16TR Tensile strength	Excellent
---------------------------------	-----------

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.