

industries3r.com

Danville office

Industries 3R inc. 55, Road 116 West Danville (Quebec) Canada J0A 1A0 Telephone: (819) 839-2793 Fax: (819) 839-2797 Toll-free: (800) 567-2728 Email: info@industries3r.com

Montreal office

Industries 3R inc. 1479, Begin street Ville St-Laurent (Quebec) Canada H4R 1V8 Telephone: (514) 333-3971 Fax: (514) 333-7224 Email: info@industries3r.com

GPO-3 GPO-3

This GPO-3 is a fiberglass reinforced thermoset polyester electrical grade sheet. This composite has an excellent combination of high strength, flame resistance and low smoke generation. This makes it ideal as a flame arc/track resistant electrical insulation.



APPLICATIONS

This composite is ideal for flame arc/track resistant electrical insulation such as insulators, used as bus bar supports, transformer parts and switchgear insulators.

SPECIFICATIONS

Physical properties

| Tensile strength (ASTM D-638) Psi | 8000 |
|---|--------|
| Compressive Strength (ASTM D-695) Psi | 33 100 |
| Flexural Strength (ASTM D-790) Psi | 22 100 |
| IZOD Impact strength (notched) (ASTM D-256) ft.lb/in. | 8.9 |

Electrical properties

| Electrical Strength - Perpendicular S/T in Air (ASTM D-149) Vpm | 450 |
|--|-----|
| Arc Resistance (ASTM D-495) Sec. | 180 |

Thermal Properties

| Coefficient of Thermal Expansion (ASTM D-696) | 2 |
|---|---|
| (in./in.°C) x 10-5 | |

| Thermal Conductivity (ASTM C 177) | 1.9 |
|--|-------|
| Dissipation Factor, MHz (ASTM D-150) | 0.010 |
| Electrical Strength - Parallel S/S in Oil (ASTM D-149) | 47 |

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.