



industries3r.com

Danville office

Industries 3R inc.
55, Road 116 West
Danville (Quebec)
Canada J0A 1A0

Telephone: (819) 839-2793
Fax: (819) 839-2797
Toll-free: (800) 567-2728
Email: info@industries3r.com

Montreal office

Industries 3R inc.
1479, Begin street
Ville St-Laurent (Quebec)
Canada H4R 1V8

Telephone: (514) 333-3971
Fax: (514) 333-7224
Email: info@industries3r.com

WRI SPIRAL GASKETS

Designed for elevated vacuum pressures and temperatures, this gasket is made as the WR style for which an internal metal ring has been added. This ring fills the space between the flanges, avoiding turbulence in the flow of the fluid or as a protection against corrosion or erosion. It is also used as a compression limit when the seating stress is greater than 30 000 psi (210 Mpa).

Also, gaskets with PTFE filler have a tendency to buckle inward thus the use of an inner ring is recommended.



APPLICATIONS

The WR type gaskets are suitable for applications that have pressure and temperature variations. They are also used to seal in processes where fluid pressures vary.

SPECIFICATIONS

Technical Data

Filler material	
Mica/Graphite (Pink)	
• Maximum temperature	232°C (450°F)
Graphie flexible (Grey)	
• Maximum temperature	450°C (840°F)
PTFE (White)	
• Maximum temperature	260°C (500°F)

N.B. The information presented may differ from practice. We recommend conducting tests according to the conditions of use. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products. The data is subject to certain variations without notice.